

SNOW MELT, FLOORWARMING AND FROST HEAVE PREVENTION MINERAL INSULATED HIGH TEMPERATURE HEAT TRACING CABLE

TYPE MIC WITH INCOLOY SHEATH

CAT.NO.	WEIGHT		M	PRICE	
	KG/M	LB/FT			FT
K-MIC	0.10	0.07	29.51		9.00
B-MIC	0.33	0.22	42.13		12.84
A-FORM-32A	0.45	1.00		553.44	
A-FORM-40A	1.82	4.00		693.65	
E-FORM-32A	0.91	2.00		774.80	
E-FORM-40A	3.64	8.00		1055.22	

PRICING EXAMPLE

SB A 750B 100 07	PRICE
HOT SECTION (100FT X \$12.84/FT)	1284.00
A-FORM 32A	553.44
TOTAL PRICE	1837.44

SPECIAL FEATURE ADDERS USE APPLICABLE PREFIX

PREFIX	DESCRIPTION	PRICE
P	PULLER EYE. Two conductor cable only attached to end termination	111.15
U	UL APPROVAL TAGGING	CONSULT SBA
X	SPECIAL ASSEMBLY. CSA tagging, non standard pigtails	CONSULT SBA
N/A	LONGER COLD SECTION LENGTH. Specify with catalog description. Adder per foot (0.3m) over 7 foot (2.13m) std cold section	12.56

COMPONENTS

CAT.NO.	DESCRIPTION	WEIGHT		PRICE
		KG	LB	
SS480	STAINLESS STEEL WIRE	2.27	5.00	105.28
HTA	HIGH TEMPERATURE ADAPTER	---	---	139.43

CONTROLS

CAT.NO.	DESCRIPTION	WEIGHT		PRICE
		KG	LB	
TLE-3120-1P	THERMOSTAT LINE/AMBIENT IN NEMA 3 ENCL. RANGE OF 20 TO 120°F (-7 TO 50°C)	0.70	1.54	250.47
SMMC-3	CONTROL PANEL	5.00	11.00	3560.75
SMAS-1	SNOW SENSOR (USE WITH SMMC-3)	0.91	2.00	657.20
SMPS-1	PAVEMENT SENSOR (USE WITH SMMC-3)	0.91	2.00	872.68
SS-01	SNOW SWITCH	0.45	0.99	592.56
LCD-1	SNOW SWITCH	0.91	2.00	CONSULT SBA

Caution: The use of GLCB'S is required at all times for all heat trace applications.